



## PHYSICAL

Lengths	6in (158.70mm) / 1ft (304mm) / 4ft (1.22m) / 8ft (2.44m)
Applications	Cove, Accent & Indirect General Illumination
Construction	Pure Aluminum Body, ABS Self-Locking Mounting Bracket and Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	Moda Aluminum Heat Sink
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Humidity	0-95% Non Condensing

## SPECIFICATIONS

	Lumens per ft	Efficacy per ft (120v)	Efficacy per ft (277v)
RED SO/HO	168 - 336	34	26
GREEN SO/HO	196 - 395	40	30
BLUE SO/HO	140 - 286	29	22
AMBER SO/HO	234 - 464	47	36
YELLOW SO/HO	215 - 430	43	33
GOLDEN YELLOW SO/HO	509 - 1015	102	78
ICE BLUE SO/HO	429 - 858	86	66
LIGHT GREEN SO/HO	490 - 980	98	75
PINK SO/HO	200 - 402	40	31
VIOLET SO/HO	194 - 388	39	30
TURQUOISE SO/HO	168 - 341	34	26

## OUTPUT

Colors	Red, Green, Blue, Amber, Yellow, Pink, Cyan, Violet, Turquoise, Ice Blue, Light Green, Golden Yellow
Beam Angle	200°
CRI	N/A
SDCM	N/A
Color Bin Tolerance	Single Bin
Lumen Maintenance	90,000 Hours L50 @ 25°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

## ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Dimming	0-10V, Electronic Low Voltage Reverse Phase Trailing Edge
Power Factor	≥ 0.90
Emergency	N/A

## DIMMING

	0-10V	ELV
6 Inch	N/A	SO only
1 Foot	SO, HO	SO, HO
4 Foot	SO, HO	SO, HO
8 Foot	N/A	SO, HO

## STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty