



PHYSICAL

Lengths	1ft (304mm) / 4ft (1.22m)
Applications	Cove, Accent & Indirect General Illumination
Construction	Pure Aluminum Body, ABS Self-Locking Mounting Bracket and Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	Moda Aluminum Heat Sink
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Humidity	0-95% Non Condensing

SPECIFICATIONS

	Lumens	Efficacy
1FT 0-10V	447.40	104.04
4FT 0-10V	1789.60	102.26

OUTPUT

CCTs	2700K to 1800K
Beam Angle	200°
CRI	98
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Single Bin
Lumen Maintenance	90,000 Hours L50 @ 25°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Dimming	0-10V
Power Factor	≥ 0.96
Emergency	N/A

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	3 Year Limited Warranty