



PHYSICAL

Lengths	6in (158.70mm) / 1ft (304mm) / 4ft (1.22m) / 8ft (2.44m)
Applications	Cove, Accent & Indirect General Illumination
Construction	Pure Aluminum Body, ABS Self-Locking Mounting Bracket and Lens
Ingress Protection	Dry/Damp Location IP52
Thermal Management	Moda Aluminum Heat Sink
Fixture Connections	Integral Male & Female Connectors
Operating Temperature	-40°F ~ 122°F (-40°C ~ 50°C)
Storage Temperature	-40°F ~ 176°F (-40°C ~ 80°C)
Humidity	0-95% Non Condensing

SPECIFICATIONS

	Lumens	Efficacy (120v)	Efficacy (277v)
6IN SO ELV	164 - 223	58 - 80	36 - 50
1FT SO 0-10V	337 - 502	67 - 100	52 - 77
1FT HO 0-10V	674 - 1004	67 - 100	52 - 77
1FT SO ELV	337 - 502	67 - 100	52 - 77
1FT HO ELV	674 - 1004	67 - 100	52 - 77
4FT SO 0-10V	1357 - 1955	71 - 103	68 - 98
4FT HO 0-10V	2714 - 3915	68 - 98	52 - 75
4FT SO ELV	1357 - 1955	71 - 103	68 - 98
4FT HO ELV	2714 - 3915	68 - 98	52 - 75
8FT SO ELV	2578 - 3715	68 - 98	64 - 93
8FT HO ELV	5156 - 7430	64 - 93	50 - 71

OUTPUT

CCTs	2200K, 2700K, 3000K, 3500K, 4000K
Beam Angle	200°
CRI	96 - 98
SDCM	2-Step MacAdam Ellipse
Color Bin Tolerance	Single Bin
Lumen Maintenance	90,000 Hours L50 @ 25°C 70,000 Hours L50 @ 50°C
Testing Data	Light Data LM-79-08 & LM-80-08

ELECTRICAL

Input Voltage	100-277V AC 50Hz/60Hz
Dimming	0-10V, Electronic Low Voltage Reverse Phase Trailing Edge
Power Factor	≥ 0.90
Emergency	N/A

DIMMING

	0-10V	ELV
6 Inch	N/A	SO only
1 Foot	SO, HO	SO, HO
4 Foot	SO, HO	SO, HO
8 Foot	N/A	SO, HO

STANDARDS & CERTIFICATIONS



Certification	Tested to UL & CSA by Intertek For Use in USA & CANADA. Exceeds ANSI C78.377-2015, CE, C-Tick, RoHS, & WEEE Compliant.
Class	1
Warranty	5 Year Limited Warranty