

modaLIGHT[®]

SPECIFICATION

MP88 DRIVER

Specification grade 12v DC 150w LED driver. Universal input 100-277v AC for worldwide use. 0-10v dimmable. Durable steel construction matte black finish. Quality construction by MODA engineers ensures long life. Fully potted. Ergonomic design. Built-in active PFC function. Fully protected from Over Current, Short Circuit and Over Temperature. Cooling by free air convection. IP66. Tested by UL.



OUTPUT

DC Voltage	12v
Rated Current	1.25A - 12.5A
Rated Power	150w
Efficiency (Typ.)	90.0%
Dimming	0 - 10v

INPUT

Voltage Range	100 - 277v AC
Frequency Range	50 / 60 Hz
Power Factor	< 0.95
Input Current	1.40A at 120v AC / 0.60A at 277v AC

PROTECTION

Open Current	Yes
Short Circuit	Yes
Surge Protection	Yes
Over Temperature	TCase: Max 194° (90° C) Type: Shutdown Mode (Re-power on to recover)

STANDARDS & CERTIFICATIONS

Safety Standards	UL8750, CSA C22.2 No. 107.1 CAN/CSA-C22.2 No. 250.13-12
RoHS	Compliant
Class	1
Warranty	5 Year Limited Warranty

Project Name:

Notes:

PHYSICAL


Dimensions	Length 9 1/2" (241mm) Width 2 3/5" (67mm) Height 1 3/5" (40.5mm)
Weight	2.40 lbs (1.08kg)
Construction	Steel Construction, Fully Potted
Thermal Management	Free Air Convection

ENVIRONMENT

Location	Wet Location Rated IP66 *Exposed wires must be encased in enclosure.
Operation Temp.	- 40° F ~ 167° F (- 40° C ~ 75° C)
Operation Humidity	0% ~ 100%
Storage Temp.	- 40° F ~ 176° F (- 40° C ~ 80° C)
Storage Humidity	0% ~ 90% RH

Note: With constant development of LED technology please refer to our website for current technical data

DIMENSIONS



MODA TECHNOLOGY

modaDRIVER™

STANDARDS & CERTIFICATIONS



Due to continuous improvements and innovations, specifications may change without notice. Please refer to our website for current technical data. These figures are provided as a guideline only and may vary with differing power supplies and installations. All rights reserved. E&OE.

VDC20172710
955 White Drive Las Vegas, NV 89119 | T: 702 407 7775
F: 702 407 7773 | www.modalight.com | © Copyright 2016