























# modaLIGHT®

## STARE & COMPARE

















### FLEXIBLE LINEAR

FPCB	Product	Lumens / Ft	Input Voltage	Max Run	IP Rating	Cuttable	Energy Consumption	CRI	Supplied Length
	AQUA EDGE	313.34 lm / ft	24V DC	30 ft (150W)	67	1 1/5"	1.49 w / ft	82	16' 4 4/5"
	AQUAFLEX DYNAMIC WHITE	241.54 lm / ft	12V DC	46 ft (132W)	67	2"	2.56 w / ft	82	16' 4 4/5"
	AQUAFLEX HCRI	158.42 lm / ft	12V DC	96 ft (150W)	67	2"	1.4 w / ft	94	19' 8 1/5"
	AQUAFLEX RUBY	136.11 lm / ft	12V DC	61 ft (150W)	67	2"	2.2 w / ft	72	19' 8 1/5"
	AQUAFLEX VOODOO	2.27 lm / ft	12V DC	110 ft (150W)	67	2"	1.23 w / ft	N/A	19' 8 1/5"
	ECOFLEX HCRI	158.65 lm / ft	12V DC	96 ft (150W)	20	2"	1.4 w / ft	93	16' 4 4/5"
	EDGE	336.21 lm / ft	24V DC	30 ft (150W)	20	1 1/5"	1.49 w / ft	82	16' 4 4/5"
	FLATFLEX	311.13 lm / ft	24V DC	40 ft (150W)	40	4"	3.41 w / ft	82	150'
	FUSIONFLEX	108.74 lm / ft	12V DC	41 ft (132W)	20	2"	3.71 w / ft	85	16' 4 4/5"
	MINI AQUAFLEX	189.59 lm / ft	12V DC	65 ft (150W)	67	1"	2.07 w / ft	82	16' 4 4/5"
	MINI STARFLEX	189.59 lm / ft	12V DC	65 ft (150W)	20	1"	2.07 w / ft	82	16' 4 4/5"
	LINEARFLEX HCRI	94.83 lm / ft	24V DC	96 ft (150W)	67	6.5"	1.4 w / ft	94	98' 5 1/10"
	POWERFLEX HCRI	318.86 lm / ft	12V DC	19 ft (150W)	20	2"	4.3 w / ft	94	19' 8 1/5"
	STARFELX DYNAMIC WHITE	241.54 lm / ft	12V DC	46 ft (132W)	20	2"	2.56 w / ft	82	16' 4 4/5"
	STARFLEX HCRI	139.67 lm / ft	12V DC	96 ft (150W)	20	2"	1.4 w / ft	94	19' 8 1/5"
	STARFLEX RUBY	136.11 lm / ft	12V DC	61 ft (150W)	20	2"	2.2 w / ft	72	19' 8 1/5"
	STARFLEX VOODOO	2.27 lm / ft	12V DC	110 ft (150W)	20	2"	1.23 w / ft	N/A	19' 8 1/5"
	SUPER AQUAFLEX HCRI	394.18 lm / ft	12V DC	28 ft (150W)	67	1"	5.8 w / ft	93	16' 4 4/5"
	SUPER FUSIONFLEX	207.38 lm / ft	12V DC	32 ft (132W)	20	2"	3.71 w / ft	89	16' 4 4/5"
	SUPERFLEX HCRI	403.18 lm / ft	12V DC	22 ft (150W)	20	1"	5.8 w / ft	93	16' 4 4/5"
	SUPERFLEX HO	772.21 lm / ft	24V DC	14 ft (150W)	20	2"	12.10 w / ft	85	8'
	X-FLEX HCRI	503.67 lm / ft	12V DC	17 ft (150W)	20	1/2"	7.6 w / ft	94	16' 4 4/5"








\*All products can be dimmed by using MODA LIGHT 0-10V & Magnetic Low Voltage Drivers. All products can be controlled using MODA LIGHT DMX 512 Controllers & Interface.

© Copyright 2017 • 955 White Drive, Las Vegas, NV 89119 • T: 702 407 7775 • F: 702 407 7773 • www.modalight.com

RGB

FPCB	Product	Lumens / Ft	Input Voltage	Max Run	IP Rating	Cuttable	Energy Consumption	RGB/ CRI	Supplied Length
	RGB AQUA EDGE	159.79 lm / ft	24V DC	40 ft (150W)	67	4"	5.12 w / ft		16' 4 4/5"
	RGB AQUAFLEX	77.88 lm /ft	24V DC	40 ft (150W)	67	4"	3.40 w / ft		13' 1 1/2"
	RGBW AQUAFLEX	206.68 lm / ft	24V DC	40 ft (150W)	67	6 1/2"	3.82 w / ft		16' 4 4/5"
	RGB EDGE	159.79 lm / ft	24V DC	27 ft (150W)	20	4"	5.12 w / ft		16' 4 4/5"
	RGB FLATFLEX	96.45 lm / ft	24V DC	14 ft (150W)	40	4"	3.09 w / ft		150'
	RGB LINEARFLEX	28.43 lm / ft	24V DC	40 ft (150W)	68	9 4/5"	1.77 w / ft		32' 9 7/10"
	RGB STARFLEX	77.88 lm / ft	24V DC	40 ft (150W)	20	4"	3.40 w / ft		13' 1 1/2"
	RGBW STARFLEX	206.68 lm / ft	24V DC	35 ft (150W)	20	6 1/2"	3.82 w / ft		16' 4 4/5"

SUPER NEON FAMILY

FPCB	Product	Lumens / Ft	Input Voltage	Max Run	IP Rating	Cuttable	Energy Consumption	RGB/ CRI	Supplied Length
	RGB SUPER NEON X DOME	48.02 lm / ft	24V DC	16 ft (150W)	67	N/A	3.51 w / ft		1', 4', 8', 16'
	RGB SUPER NEON X FLAT	39.95 lm /ft	24V DC	16 ft (150W)	67	N/A	3.51 w / ft		1', 4', 8', 16'
	SUPER NEON EDGE	198.48 lm / ft	24V DC	30 ft (150W)	67	N/A	3.38 w / ft	88	1', 4', 8', 30'
	SUPER NEON X DOME	99.40 lm / ft	24V DC	30 ft (150W)	67	N/A	4.68 w / ft	88	1', 4', 8', 30'
	SUPER NEON X FLAT	127.71 lm / ft	24V DC	30 ft (150W)	67	N/A	4.68 w / ft	88	1', 4', 8', 30'

\*All products can be dimmed by using MODA LIGHT 0-10V & Magnetic Low Voltage Drivers. All products can be controlled using MODA LIGHT DMX 512 Controllers & Interface.  
© Copyright 2017 • 955 White Drive, Las Vegas, NV 89119 • T: 702 407 7775 • F: 702 407 7773 • www.modalight.com